

**What is claimed is:**

1. (Currently Amended) An operator system for a motorized barrier, comprising:
  - an operator which controls the motorized barrier, said operator ~~capable of~~ receiving wireless operational signals to control the motorized barrier;
  - a device which controls an electrical load, said device ~~capable of~~ receiving wireless operational signals to control said load; and
  - at least one transmitter ~~capable of~~ generating wireless operational signals upon a single button actuation receivable by said operator and said device for at least one of independent operation of each and collective operation of both said operator and said device.
2. (Original) The system according to claim 1, wherein said at least one transmitter is selected from a group consisting of a wall station transmitter, a remote transmitter, and a keyless entry transmitter.
3. (Original) The system according to claim 2, wherein said operator and said device both receive only the same frequency wireless signals from said at least one transmitter.
4. (Original) The system according to claim 1, wherein said device is a fixture that controls a light.
5. (Original) The system according to claim 4, wherein said fixture comprises;
  - a transceiver for at least receiving said wireless signals; and
  - a controller connected to said transceiver, wherein said controller validates said wireless signal and controls said light if said wireless signal is validated.
6. (Original) The system according to claim 5, wherein said fixture further comprises:
  - a program button operative with said controller;
  - a memory device associated with said controller, and

wherein actuation of said program button places said controller in a learn mode such that any valid signal received while in said learn mode is stored in said memory device.

7. (Currently Amended) The system according to claim 6, wherein said controller is able to distinguish between ~~said~~ a group of transmitters, and wherein said at least one transmitter is selected from a group consisting of a wall station transmitter, a remote transmitter, and a keyless entry transmitter.
8. (Original) The system according to claim 7, wherein said remote transmitter has plurality of function buttons, and wherein actuation of a first button of said remote transmitter in said learn mode designates said first button as a barrier command, and wherein actuation of any other button of said remote transmitter while in said learn mode designates said other button as a work light command.
9. (Currently Amended) The system according to claim 8, wherein generation of said barrier command by said at least one transmitter is separately and directly receivable by said operator and said fixture for illumination of said light for only a predetermined period of time.
10. (Original) The system according to claim 9, wherein generation of said work light command by said at least one transmitter illuminates said light if in an off condition, and returns said light to said off condition only if no door command had been previously received within a designated time period.
11. (Original) The system according to claim 10, wherein generation of said barrier command is specifically limited to valid first buttons learned from said remote transmitters, said keyless entry transmitter, and selected buttons from said wall station transmitters.
12. (Original) The system according to claim 11, wherein said selected buttons of said wall station transmitters include an up/down button, a delay close button, a pet

height button, and a door profile button.

13. (Original) The system according to claim 10, wherein generation of said barrier command while said light is illuminated as a result of receiving said work light command causes said controller to turn said light off after a predetermined period of time.
14. (Original) The system according to claim 1, wherein said device is a switch that controls a load.
15. (Original) The system according to claim 14, wherein said switch further comprises:
  - a transceiver for at least receiving said wireless signals; and
  - a controller connected to said transceiver, wherein said controller validates said wireless signal and control said load if said wireless signal is validated
16. (Original) The system according to claim 15, wherein said switch further comprises:
  - a program button operative with said controller;
  - a memory device associated with said controller, and
  - wherein actuation of said program button places said controller in a learn mode such that any valid signal received while in said learn mode is stored in said memory device.
17. (Original) The system according to claim 16, wherein said controller is able to distinguish between said at least one transmitter, and
  - wherein said at least one transmitter is selected from a group consisting of a wall station transmitter, a remote transmitter and a keyless entry transmitter.
18. (Original) The system according to claim 17, wherein said operator is capable of generating wireless signals and wherein said controller is able to distinguish operator wireless signals and transmitter wireless signals.

19. (Original) The system according to claim 18, wherein said switch further comprises:
- an on button connected to said controller;
  - an off button connected to said controller;
  - a switch on indicator connected to said controller; and
  - a switch off indicator connected to said controller;
  - a memory device associated with said controller; wherein
- one of said buttons function as a program button operative with said controller when actuated for a predetermined period of time to place said controller in a learn mode such that any valid signal received in said learn mode is stored in said memory device.
20. (Original) The system according to claim 19, wherein the learning of a valid transmitter wireless signal and a valid operator wireless signal by said controller initiates illumination of one of said indicators in a predetermined manner.
21. (Currently Amended) The system according to claim 20, wherein receipt of said valid wireless signal by said controller when not in said learn mode causes said switch to turn said load on if previously off ~~for a predetermined period of time~~.
22. (Original) The system according to claim 20, wherein receipt of said valid wireless signal by said controller when not in said learn mode causes said switch to turn said load off if previously on.
23. (Original) The system according to claim 19, wherein said switch on indicator is active when said load is active and said switch off indicator is active when said load is inactive.
24. (Original) The system according to claim 23, wherein actuation of said on button turns said load on and precludes said controller from receiving any wireless signals, and wherein actuation of said off button turns said load off and allows said controller to receive any valid wireless signals.

25. (Canceled)
26. (Currently Amended) The system according to claim [[25]] 1, wherein said operator and said device both receive wireless signals from said at least one transmitter having only the same frequency.
27. (Currently Amended) The system according to claim [[25]] 1, wherein said device is a fixture that controls a light.
28. (Currently Amended) The system according to claim [[25]] 1, wherein said device is a switch that controls a load.
29. (Currently Amended) The system according to claim [[25]] 1, wherein said at least one transmitter generates said wireless signals at a first frequency and said operator generates wireless signals at a second frequency.
30. (Original) The system according to claim 29, wherein said operator generates said wireless signals at said second frequency upon receipt of said wireless signals at said first frequency.
31. (Currently Amended) The system according to claim [[25]] 1, wherein said operator generates said wireless signals at a first frequency upon receipt of said wireless signals from said at least one transmitter at said first frequency.
32. (Canceled)
33. (Currently Amended) The system according to claim [[32]] 1, wherein said at least one device comprises:  
a controller; and  
a program button connected to said controller, wherein actuation of said program button places said controller in a learn mode for a predetermined period of time, and wherein actuation of said at least one function button during said

predetermined period of time associates said at least one function button with said electrical load.

34. (Original) The system according to claim 33, wherein said at least one function button is associated with more than one said device.
35. (Original) The system according to claim 33, wherein said at least one device is associated with more than one said transmitter.
36. (Original) The system according to claim 33, wherein said at least one function button is associated with more than one device; and wherein said at least one device is associated with more than one said transmitter.
37. (Original) The system according to claim 33, further comprising:
  - a memory device associated with said controller for storing a valid signal received during said learn mode.
38. (Original) The system according to claim 33, wherein said at least one device is a fixture that controls a light.
39. (Original) The system according to claim 33, wherein said at least one transmitter is selected from a group consisting of a wall station transmitter, a remote transmitter, and a keyless entry transmitter.
40. (Original) The system according to claim 33, wherein said device is a switch that controls a load.
41. (Original) The system according to claim 40, wherein said switch further comprises:
  - a transceiver for at least receiving said wireless signals; and
  - said controller connected to said transceiver, wherein said controller validates said wireless signal and controls said load if said wireless signal is

validated

42. (Original) The system according to claim 41, wherein said switch further comprises:
- a memory device associated with said controller such that any valid signal received while said controller is in said learn mode is stored in said memory device.
43. (Original) The system according to claim 42, wherein said controller is able to distinguish between said at least one transmitter, and
- wherein said at least one transmitter is selected from a group consisting of a wall station transmitter, a remote transmitter and a keyless entry transmitter.
44. (Original) The system according to claim 43, wherein said switch further comprises:
- an on button connected to said controller;
  - an off button connected to said controller;
  - a switch-on indicator connected to said controller; and
  - a switch-off indicator connected to said controller;
  - a memory device associated with said controller; wherein
- one of said buttons function as a program button operative with said controller when actuated for a predetermined period of time to place said controller in a learn mode such that any valid signal received while in said learn mode is stored in said memory device.
45. (Original) The system according to claim 44, wherein the learning of a valid transmitter wireless signal and a valid operator wireless signal by said controller initiates illumination of one of said indicators in a predetermined manner.
46. (Currently Amended) The system according to claim 45, wherein receipt of said valid wireless signal by said controller when not in said learn mode causes said switch to turn said load on if previously off ~~for a predetermined period of time.~~

47. (Original) The system according to claim 45, wherein receipt of said valid wireless signal by said controller when not in said learn mode causes said switch to turn said load off if previously on.
48. (Original) The system according to claim 44, wherein said switch-on indicator is active when said load is active and said switch off indicator is active when said load is inactive.
49. (Original) The system according to claim 48, wherein actuation of said on button turns said load on and precludes said controller from receiving any wireless signals, and wherein actuation of said off button turns said load off and allows said controller to receive any valid wireless signals.
50. (New) A system for controlling a motorized barrier and a device, comprising:  
an operator which controls the motorized barrier, said operator receiving and transmitting wireless operational signals;  
a device which controls an electrical load, said device receiving and transmitting wireless operational signals; and  
at least one transmitter generating wireless operational signals receivable by one of said operator and said device for actuation thereof, wherein one of said operator and said device subsequently transmits another wireless operational signal to the other of said operator and said device.
51. (New) The system of claim 50 wherein said at least one transmitter generates wireless operational signals in one frequency range receivable by one of said operator and said device, wherein one of said operator and said device subsequently transmits wireless operational signals in another frequency range different from said one frequency range to the other of said operator and said device.
52. (New) The system according to claim 51, wherein said device is a light fixture.



53. (New) The system according to claim 51, wherein said device is a switch that controls a load.